

AMENDMENTS TO THE CLAIMS

1 1. **(Previously amended)** A massager mountable in a spa wall, said spa wall having a
2 massager opening therein, a spa surface, and an outer surface, the massager
3 comprising:

4 a main housing having a wall mounting end supportable in said massager
5 opening, an exterior end opposite the wall mounting end, and a main housing interior
6 space;

7 a gear housing having a turbine end and a massager end, said gear housing
8 being removably supported in said interior space of said main housing, wherein said
9 massager end resides proximal to said spa surface, said gear housing being removable
10 from said main housing interior space through said main housing wall mounting end;

11 a turbine residing at said turbine end of said gear housing; and

12 a rotating massager mechanically coupled to said turbine and residing proximal
13 to said massager end of said gear housing, wherein said rotating massager extends
14 past the spa surface and into the spa.

2. **(Original)** The massager of Claim 1, wherein the gear housing is threadably
secured to said main housing.

3. **(Original)** The massager of Claim 1, wherein the turbine is mechanically coupled to
said rotating massager by gears.

4. **(Original)** The massager of Claim 3, wherein the turbine is mechanically coupled to
said rotating massager by at least one planetary gear assembly.

5. **(Original)** The massager of Claim 4, wherein the at least one planetary gear
assembly comprises two planetary gear assemblies in series.

6. **(Original)** The massager of Claim 3, wherein the rotating massager is mechanically coupled to turn at approximately one twenty fifth the rate of rotation of the turbine.

7. **(Original)** The massager of Claim 1, wherein the rotating massager is adapted to rotate at approximately fifty to approximately eighty Revolutions Per Minute (RPM).

8. **(Original)** The massager of Claim 1, further including a water inlet and a water outlet disposed behind said outer surface.

1 9. **(Previously amended)** The massager of Claim 8, further including a turbine
2 housing attached to said main housing exterior end, said turbine housing including the
3 water inlet and the water outlet, wherein the gear housing including the turbine is
4 removable from said main housing interior space through said main housing wall
5 mounting end without removing the turbine housing.

10. **(Original)** The massager of Claim 1, wherein the rotating massager comprises a plurality of balls held by a rotating ball plate adapted to rotate about a central axis of said gear housing.

11. **(Original)** The massager of Claim 7, wherein the plurality of balls comprises three balls.

12. **(Original)** The massager of Claim 7, further including a boot covering the plurality of balls.

13. **(Original)** The massager of Claim 1, wherein the gear housing includes a handle portion graspable from the gear housing massager end whereby the gear housing may be manipulated to be released from said main housing.

1 **14. (Previously amended)** A method for providing a massage, the method
2 comprising:
3 injecting a flow of water through a turbine residing behind a spa wall;
4 directing the flow of water against blades of a turbine to spin the turbine;
5 coupling the rotation of the turbine to a pinion gear of a planetary gear set; and
6 rotationally coupling the rotation of the pinion gear through the planetary gear set
7 to a rotating massager residing proximal to a spa wall, wherein the coupling through the
8 planetary gear set reduces the rotational speed of the rotating massager relative to the
9 turbine.

15. **(Original)** The method of Claim 14 wherein spinning a turbine shaft comprises
spinning a turbine shaft at from approximately 1500 Revolutions Per Minute (RPM) to
approximately 2000 RPM.

16. **(Original)** The method of Claim 14 wherein rotationally coupling the turbine shaft
to a massager comprises rotating the massager at from approximately 50 Revolutions
Per Minute (RPM) to approximately 80 RPM.

17. **(Original)** The method of Claim 14, wherein rotationally coupling comprises
rotationally coupling the turbine to the massager wherein the massager rotates at
approximately one twenty fifth the angular velocity of the turbine.

18. - 20. cancelled